

Umlenkräder, 2-teilig



für Ketten der Serien 1050 – 1055 – 1060 – 2250

Nabenbreite: 45 mm, für Kettenteilung: 25,4 mm | 1"

Split idler sprockets

for chainbelts series: 1050 – 1055 – 1060 – 2250

Hub width: 45 mm | 1.77 inch, Linear pitch: 25.4 mm | 1 inch



Artikel Nr. Part No.	Zähnezahl No. of teeth	Bohrung + 0,3 mm Bore + 0,3 mm DF in mm	Kopfkreis Outer dia. DP in mm inch	Gewicht Weight kg per St. pc.
1050-16-25-UPT	16	25	132,5 5.22	0,45
1050-16-30-UPT		30		
1050-16-35-UPT		35		
1050-16-40-UPT		40		
1050-16-50-UPT		50		
1050-18-25-UPT	18	25	149,2 5.87	0,50
1050-18-30-UPT		30		
1050-18-35-UPT		35		
1050-18-40-UPT		40		
1050-18-50-UPT		50		

Material:

Äußerst verschleißfestes Gußpolyamid, Schrauben und Paßstifte aus Edelstahl, Gewindebuchsen Messing vernickelt.

Für metrische Wellen.

Bordscheiben aus Edelstahl und Polyamid verfügbar.

Abmessungen und Toleranzen siehe „Technische Informationen“ am Ende dieses Kapitels.

Weitere Abmessungen auf Anfrage möglich.

Umlenkräder, 2-teilig



für Kunststoff-Mattenketten der Serie 1005

Nabenbreite: 38 mm, für Kettenteilung: 25,4 mm | 1"

Split idler sprockets

for modular belts series: 1005

Hub width: 38 mm | 1.5 inch, Linear pitch: 25.4 mm | 1 inch



Artikel Nr. Part No.	Zähnezahl No. of teeth	Bohrung + 0,3 mm Bore + 0,3 mm DF in mm	Kopfkreis Outer dia. DP in mm inch	Gewicht Weight kg per St. pc.
1005-15-30-UPT	15	30	119,5 4.70	0,42
1005-15-40-UPT		40		
1005-16-30-UPT	16	30	126,0 4.96	0,55
1005-16-40-UPT		40		
1005-18-25-UPT	18	25	145,3 5.72	0,60
1005-18-30-UPT		30		
1005-18-40-UPT		40		
1005-21-30-UPT	21	30	169,7 6.68	0,70
1005-21-40-UPT		40		

Material:

Super tough cast-polyamide, screws and parallel dowel pins in stainless steel, inserts in nickel plated brass.

For metric shafts.

Guide rings available in stainless steel and polyamide.

For dimensions and tolerances see „Technical Information“ at the end of this chapter.

Further dimensions upon request.

Hygienic Design

